

Amendments to the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1-25. (cancelled)

26. (new) A method of transmitting a first parallel data stream over a fiber optic channel, comprising:

- converting the first parallel data stream into a plurality of second parallel data streams;
- parallel process converting the plurality of second parallel data streams into a plurality of analog signals;
- combining the plurality of analog signals into a single analog signal;
- converting the single analog into an optical signal; and
- coupling the optical signal to the fiber optic channel.

27. (new) A method as in claim 26 wherein the parallel process converting the plurality of second parallel data streams into a plurality of analog signals further comprises:

- encoding the plurality of second parallel data streams into symbols in a plurality of symbol encoders;
- converting the symbols into a plurality of transformed values in an inverse Fourier transformer; and
- converting the transformed values into analog representations in a plurality of digital to analog converters.

28. (new) A method as in claim 26 wherein the parallel process converting the plurality of second parallel data streams into a plurality of analog signals further comprises:

- modulating the second parallel data streams in a plurality of modulators;
- mixing the modulated signals in a plurality of mixers and
- filtering the mixed signals in a plurality of band pass filters.

29. (new) A method as in claim 26 wherein the converting the first parallel data stream into a

plurality of second parallel data streams comprises accepting the first parallel data stream from an interface selected from the interfaces consisting of a ten gigabit media independent interface (XGMII) and a ten gigabit extended Attachment Unit Interface (XAUI).

30. (new) A method as in claim 26 wherein the parallel process converting the plurality of second parallel data streams into a plurality of analog signals further comprises:

encoding the plurality of second parallel data streams in a plurality of symbol encoders;
and
converting the encoded values into analog representations in a plurality of digital to analog converters.

31. (new) A method of converting an optical signal received from a fiber optic channel into a parallel data stream, comprising:

converting the optical signal received from the fiber optic channel into an analog electrical signal;
converting the analog electrical signal into a plurality of baseband signals; and
converting the plurality of baseband signals into a parallel data stream.

32. (new) A method as in claim 31 wherein the parallel process converting the analog electrical signal into a plurality of baseband signals comprises mixing the analog electrical signal with a plurality of mixing frequencies to produce a plurality of baseband signals.

33. (new) A method as in claim 32 wherein the parallel process converting the analog electrical signal into a plurality of baseband signals comprises mixing the analog electrical signal with a plurality of mixing frequencies to produce a plurality of baseband signals further comprises filtering the plurality of signals mixed with the plurality of mixing frequencies to produce a plurality of baseband signals.

34. (new) A method as in claim 31 wherein the parallel process converting the analog electrical signal into a plurality of baseband signals comprises:

converting the analog electrical signal into a plurality of symbols in a Fourier transformer; and
decoding the plurality of symbols in a plurality of decoders to produce a parallel data

stream.

35. (new) A method as in claim 31 wherein the converting of the analog electrical signal into a plurality of baseband signals further comprises:

- sampling and holding successive values of the analog electrical signal;
- providing the held analog values to a plurality of A/D converters; and
- converting the held values to a plurality of baseband signals.

36. (new) A method as in claim 31 wherein the parallel process converting of the analog electrical signal in a plurality of baseband signals further comprises:

- sampling and holding successive values of the analog electrical signal;
- providing the held values to a single A/D converter; and
- converting the held values to a plurality of baseband digital signals.

37. (new) A method as in claim 35 wherein the converting of the held values to a plurality of baseband signals further comprises time interleaving the converting of the held values.

38. (new) A method of transmitting and receiving a first parallel data stream over a fiber optic channel, comprising:

- converting the first parallel data stream into a plurality of second parallel data streams;
- parallel process converting the plurality of second parallel data streams into a plurality of analog signals;
- combining the plurality of analog signals into a single analog signal;
- converting the single analog signal into an optical signal;
- coupling the optical signal onto the fiber optic channel;
- converting the optical signal received from the fiber optic channel into an analog electrical signal;
- parallel process converting the analog electrical signal into a third plurality of parallel digital signals; and
- converting the third plurality of parallel digital signals into a fourth parallel data stream.

39. (new) A method of converting an optical signal received from a fiber optic channel,

Appln. No.: Unassigned
Prelim. Amdt. dated ???????

comprising:

- converting the optical signal received from a fiber optic channel into an analog electrical signal;
- providing the analog electrical signal to a plurality of A/D converters; and
- converting the analog electrical signal to a plurality of digital signals.